



CL828-xx Aero cleat Instructions

Compact cleats that are rigged on a rope. Nylon and alloy versions.
 Easy to rig and adjust. Strong and wear resistant.
 Ideal for forestay tensioning, kitesurfing, sports netting, sun sails, canvas structures, tie-downs, radio masts and aerials.

Standard rigging for all cleats
 2:1 advantage

3 - 4mm
 (1/8" - 5/32") Ø

Move cleat along the rope by hand. No tools required.

When using 3mm rope, take an extra turn round centre pillar.

CL828-63 (CL828 Aero base with black nylon CL263) 15gm. 0.5oz.

CL828-68 (CL828 Aero base with alloy CL268 silver) 21gm. 0.75oz.

CL828-68AN (CL828 Aero base with alloy CL268 hard anodised)

Rigs with 2:1 advantage

Rig like this to make a loop.

Rigging like this = no rope tail.

CL828-70 (CL828 Aero base with alloy CL270 silver) 24gm. 0.8oz.

CL828-70AN (CL828 Aero base with alloy CL270 hard anodised)

CL828-70 Rigged with 4:1 advantage for running rigging

CL828-70 Rigged with 4:1 advantage for standing rigging

4:1 advantage

Splice
 Sew
 Knot

CL828-77 (CL828 Aero base with alloy CL277 silver) 23gm. 0.85oz.

CL828-77AN (CL828 Aero base with alloy CL277 hard anodised)

CL828-77 Rigged with 2:1 advantage

Rig like this to make a loop.

Rigging like this = no rope tail.